



YFK-T30S (PP wire drawing material)

Specifications

Appearance	White or light yellow columnar particles
Volatile Loss %	<= 2.0
Particle Size (mm)	2.0 ~ 3.0
Acidity Value (mg KOH/g)	<= 1.0
Stacking Density (g/cm³)	0.40 ~ 0.60

Usage Notes

Ingredients	Antioxidants, auxiliary antioxidants and acid scavenger in a certain proportion through special process.
Properties	It is a high-performance antioxidant with stable properties, non-toxic, odorless, and insoluble in organic solvents such as toluene and methanol at room temperature. The additive is supplied as white or light-yellow columnar particles.
Performance	It provides outstanding processing stability and long-term protection for polyolefins, while significantly reducing dust generation during processing to minimize operator exposure and improve workplace safety.
Applications	It is a high-performance polypropylene additive with good light stability. It provides excellent processing stability and color retention for polypropylene T30S wire-drawing materials and exhibits strong anti-oxidation performance even at low dosages.
Storage	This product is stable under normal conditions and does not have any special storage requirements. However, it should be protected from moisture and heat.
Packaging	The product is packaged in cartons with plastic liners or in cardboard barrels with plastic liners. The net weight per unit is 25 kg. Customized packaging is available.